



# KEM PROOF EWC (BLACK)

## Elastomeric Waterproofing Coating

Ref. WP/CO-V1-0114

### Description

KEM Proof EWC (Black) is a heavy duty bituminous elastomeric waterproofing coating product.

### Uses

- Asbestos cement roofs and around 'J' hooks
- Sunken portions of toilets
- Sewage pipes
- Plinth, foundation, basements, etc.

### Advantages

- Highly impermeable, safe, non-flammable
- Pourable consistency, hence easily brushable and prevents fungal and bacterial growth.
- Very flexible, accommodates movements in cracks, does not crack with age.
- Cold applied, user friendly
- Does not require curing
- Dries fast, ready to use with sufficient open time.

### Typical Properties

Appearance : Black after drying.

Specific Gravity : 1.09 ± 0.02.

Viscosity : 18 to 25 poise.

### Direction for use

Clean the required surface to ensure there is no loose material or contamination before coating.

Moisten the surface adequately prior to application. Also allow surface water to evaporate.

In case of sunken slabs in toilets, bathrooms, extend the coat by 1 - 1.5 feet above the floor finish level.

Allow the first coat to dry for 4 to 5 hours, apply the second coat and allow it to dry for 48 hours. (a fibre net cloth must be sandwiched between 2 successive coats especially in the cracks of asbestos sheets).

Protect the coating from getting damaged by overlaying it with 15mm cement sand mortar.

### Coverage

15-20 sq.ft./kg for 2 coats. 200 to 300 microns DFT depending on the condition of the substrate.

### Packaging

30 kg, 50 kg, 100 kg

### Storage and Shelf life

**Storage:** Away from direct sunlight

**Shelf life:** 12 months from manufacturing date.

### Technical Service

Chembond has established itself in various fields on the basis of its dependable technical service. For this purpose, we maintain a well equipped laboratory for research & quality assurance of all products. Our experienced personnel are always on call and would always be available for product demonstrations and product performance monitoring.

#### Chembond Chemicals Limited

Chembond Centre, EL-71, MIDC,  
Mahape, Navi Mumbai, India 400 710.  
Tel.: +91 22 39213 000 , Fax: +91 22 3921 3100  
website: [www.chembondindia.com](http://www.chembondindia.com)  
e-mail: [enquiries.conschem@chembondindia.com](mailto:enquiries.conschem@chembondindia.com)

#### Limitation of Liability:

This information is based on our current level of knowledge. It is given in a good faith but it is not intended to guarantee any particular properties. The users must satisfy themselves that there are no circumstances requiring additional information or precautions or the verification of details given herein.